

Amendment to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-13 (canceled).

14. (previously presented) A gas turbine in which a rotor shaft comprises a plurality of discs each having a plurality of moving blades arranged annularly on a peripheral portion, and spacers arranged between said discs, said respective discs and spacers being arranged in an axial direction in turn, comprising:

gap portions formed between rotor axis side regions of said discs facing said spacers and adjacent spacers;

a supply flow path for supplying refrigerant for cooling to said moving blades and a recovery flow path for recovering heated refrigerant, each of said supply and recovery flow paths being provided in said rotor shaft; and

a flow path for introducing fluid into said gap portions, provided in said discs; and

wherein said recovery flow path is arranged on a more radially inner side than said supply flow path, and

said flow path for introducing fluid into said gap portion is arranged on a more radially inner side than said supply flow path.

15. (canceled)

16. (currently amended) ~~A gas turbine in which a rotor shaft comprises a plurality of discs each having a plurality of moving blades arranged annularly on a peripheral portion, and spacers arranged between said discs, said respective discs and spacers being arranged in an axial direction in turn, comprising:~~

~~—— gap portions formed between rotor axis side regions of said discs facing said spacers and adjacent spacers;~~

~~—— a supply flow path for supplying refrigerant for cooling to said moving blades and a recovery flow path for recovering heated refrigerant, each of said supply and recovery flow paths being provided in said rotor shaft; and~~

~~—— a flow path for introducing fluid into said gap portions, provided in said discs; and~~

~~—— wherein said recovery flow path is arranged on a more radially inner side than said supply flow path, and~~ A gas turbine according to claim 14, wherein the fluid introduced into said gap portions is exhausted ~~therefrom~~ into a gas flow path of said gas turbine.

17. (previously presented) A gas turbine in which a rotor shaft comprises a plurality of discs each having a plurality of moving blades arranged annularly on a

peripheral portion, and spacers arranged between said discs, said respective discs and spacers being arranged in an axial direction in turn, comprising:

gap portions formed between rotor axis side regions of said discs facing said spacers and adjacent spacers;

a supply flow path for supplying steam for cooling to said moving blades and a recovery flow path for recovering heated steam, each of said supply and recovery flow paths being provided in said rotor shaft; and

a flow path for introducing fluid into said gap portions, provided in said discs; and

wherein said recovery flow path is arranged on a more radially inner side than said supply flow path, and

said flow path for introducing fluid into said gap portion is arranged on a more radially inner side than said supply flow path.

18. (previously presented) A gas turbine in which a rotor shaft comprises a plurality of discs each having a plurality of moving blades arranged annularly on a peripheral portion, and spacers arranged between said discs, said respective discs and spacers being arranged in an axial direction in turn, comprising:

gap portions formed between rotor axis side regions of said discs facing said spacers and adjacent spacers;

a supply flow path for supplying steam for cooling to said moving blades and a recovery flow path for recovering heated steam, each of said supply and recovery flow paths being provided in said rotor shaft; and

a flow path for introducing fluid into said gap portions, provided in said discs;
and

wherein said flow path for introducing fluid into said gap portion is constructed so as to be supplied with air extracted from a compressor, and arranged on a more radially inner side than said supply flow path,

said recovery flow path is arranged on a more radially inner side than said supply flow path; and

said flow path for introducing fluid into said gap portion is arranged on a more radially inner side than said supply flow path.